



**permobil**

THE POWER OF MOBILITY™

## TOTAL CONTROL HEAD ARRAY SYSTEM EASY TO USE, TOUGH TO NOTICE

Maintaining our tradition of using innovation to enhance the lives of people needing powered mobility, our NEW Total Control Head Array System takes adjustability and versatility to the next level. With its telescoping arms and the ability to mount proximity sensors or mechanical switches virtually anywhere, the device can be easily configured to meet any control need. Plus, the Permobil head array's comfortable, minimal design allows the user to control the chair without being overwhelmed by the equipment.

**IN OTHER WORDS, YOU'LL SEE THE PERSON,  
NOT THE PRODUCT.**

### AVAILABLE CONFIGURATIONS






# permobil

THE POWER OF MOBILITY™



## Transfers Made Easy

Arms swing completely out of the way to allow for total lateral clearance.



## Enhanced Control

Two occipital sensors make large targets for more accessible activation and simplified turning.



## Plug 'N Play

Color-coded jacks on connection panel are easily connected, disconnected or re-assigned.



## A Perfect Fit

Telescoping arms can be adjusted vertically, horizontally, lengthened and shortened to custom-fit the user.

## CONFIGURATION OPTIONS

DESCRIPTION	ON CHAIR	SPARE PART	HCPCS
Base head array includes left and right proximity sensors on short lateral arms in upper position.	I105922-99-0	0055-7030A	E2330
Small occipital pad - 3" tall x 4.25" wide (80 mm x 110 mm)	I105920-99-0	0055-7028A	--
Large occipital pad - 4" tall x 6" wide (100 mm x 150 mm)	I105921-99-0	0055-7029A	--
Lateral Pad - 1.75" tall x 2.75" wide (45 mm x 70 mm) solid polyurethane positioning pad	I105912-99-0	0055-7026A	K0108
Egg switch - 1.75" tall x 2.75" wide (45 mm x 70 mm) mounted on adjustable swivel assembly.	I105919-99-0	0055-7027A	K0108
Stealth TVVB-480 backrest mounting hardware with two adjustable links	I105927-99-0 I105941-99-0 (Flipback)	1828250 1828277 (Flipback)	E1028
Stealth TVVB-480 backrest mounting hardware with two adjustable links and sub-occipital assembly	I10848	--	E1028
Stealth HMO-475 multi-axis mounting hardware with 1/2" square rod	I105925-99-0	1828246	E1028
Range adjustable proximity sensor embedded in polyurethane lateral pad	I05906-99-0 (Short Cable) I105907-99-0 (Long Cable)	0055-7023A (Short Cable) 0055-7024A (Long Cable)	K0108
Short metal re-inforced lateral arm - adjustment range 5.5" - 8" (140 mm - 205 mm)	I105937-99-0 (Left) I105938-99-0 (Right)	0055-7018A (Left) 0055-7019A (Right)	E1028
Long metal re-inforced lateral arm - adjustment range 9" - 13.5" (225 mm - 345 mm)	I105939-99-0 (Left) I105940-99-0 (Right)	0055-7020A (Left) 0055-7021A (Right)	E1028

Appearance and specifications are subject to change without notice.

TCHAS052912